

Part Number: 6508UE



Security & Sound, #22-10c, BC, CMP

# **Product Description**

Security & Sound Cable, Plenum-CMP 10-22 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

# **Technical Specifications**

# **Physical Characteristics (Overall)**

Conduc	Conductor		
AWG	Stranding	Material	No. of Conductors
22	7x30	BC - Bare Copper	10
Condu	ctor Count:		
Condu	ıctor Size:		

#### Insulation

Material	Material Trade Name	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.009 in

## Color Chart



# Outer Shield Material



### **Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.218 in	0.015 in	Yes

# **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR 16.2 Ohm/1000ft

# Capacitance



Shielding: Unshielded

#### Current



### Voltage



#### **Temperature Range**

Operating Temp Range:	0°C To +75°C
-----------------------	--------------

### **Mechanical Characteristics**

Bulk Cable Weight:	35.5 lbs/1000ft
Max Recommended Pulling Tension:	91 lbs
Min Bend Radius/Minor Axis:	2.2 in

#### **Standards**

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262 Plenum Flame Test (UL910)
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

# Part Number

Non-Plenum Number:	5508UE

### Variants

Item #	Color
6508UE 877U1000	Natural

### © 2018 Belden, Inc

# All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.