




Configuration:

CN36M		CN36M
1	_____	1
2	_____	2
3	_____	3
4	_____	4
5	_____	5
6	_____	6
7	_____	7
8	_____	8
9	_____	9
10	_____	10
11	_____	11
12	_____	12
13	_____	13
14	_____	14
15	_____	15
16	_____	16
17	_____	17
18	_____	18
19	_____	19
20	_____	20
21	_____	21
22	_____	22
23	_____	23
24	_____	24
25	_____	25
26	_____	26
27	_____	27
28	_____	28
29	_____	29
30	_____	30
31	_____	31
32	_____	32
33	_____	33
34	_____	34
35	_____	35
36	_____	36
Shield	_____	Shield

**CN36 Male**



**CN36 Male**



**Material:**

- 1.Cable: #28 36C+1+AL/MY(Beige PVC Jacket) O.D:9.0MM
- 2.Both connectors with normal type
- 3.Overall Molded with beige PVC

**Notes:**

- 1.Total Length: 3M±5CM
- 2.Color: Beige
- 3.Molded Type



<i>ITEM NO</i>	<b>AK426-3</b>	<b>(3 Meters)</b>
<i>TITLE</i>	<b>Centronics Printer Cable, CENT 36-Pin Male to CENT 36-Pin Male</b>	

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283  
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
©Copyright 2008 by Assmann Electronic Components  
All International Rights Reserved