



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00006	Connector, 2.5xL21.6 mm, audio plug 4C with metal ring, brass nickel plated	2	
2	30-00413	Wire, 4C TC, 26 AWG, 30V, 80C, 3.7 mm, shielded, PVC, 89A	1	
3	24-00104	Overmold, PVC, black	2	



**Notes:**

Electical requirement: 2 A

Hi-Pot test: 300 Vac, 0.5 mA, 1 second

Wiring Diagram		
50-00006	wire color	50-00006
A	Red	A
B	Black	B
C	Green	C
D	Yellow	D

Revision: A	Date: 1/19/2009	Description: Re-issued CUI spec as Tensility	Prepared:	Notes: RoHS and REACH compliant
A1	5/11/2009	Added connector part number	Verified:	Function test: no open, no short circuit, no intermittent
A2	8/30/2011	Updated description and part number information	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 4C 2.5mm 50-00006 plug with metal ring to same, 26 AWG, 30-00413
A3	5/6/2014	Updated description		

**TENSILITY**

tel 1.541.323.3228 800 877.670.7118  
fax 1.541.323.4202 web tensility.com

Size: A Part number: **053-0110R (CA-254CS-MM)**

Scale: 1:1 Sheet 1 of 1